# GateHaul: A Gateway Architecture using Backhauling Networks to Address the Connectivity Challenges of Embedded Systems

Spanddhana Sara, Moteen Shah, Dhairya Shah, C. Rajashekar Reddy



Figure 1: GateHaul bridges low-power networks with computing infrastructure. It provides carrier signals for low-power transmitters, while also collecting sensor data and backhauling it opportunistically to remote servers. Abstract Keywords

Significant efforts to address the energy challenges of embedded systems have resulted in the design of new low-power transmitter architectures. These transmitters utilize backscatter or tunnel diode-based mechanisms to enable low-power transmissions by delegating energy-intensive tasks to external infrastructure. However, their widespread adoption is hindered by the need for specialized deployment setups, such as the precise placement of carrier-emitting devices. To overcome this, we are developing GateHaul-a low-cost gateway architecture that provides the required carrier signal, coordinates with other gateways, collects sensor data, and backhauls the information. Notably, GateHaul can backhaul sensor data without conventional networks utilizing emerging opportunistic backhaul networks. We demonstrate an early prototype of GateHaul that collects information from backscatter and conventional devices and backhauls the collected information using Apple's FindMy network.

## **CCS** Concepts

• Networks → Programming interfaces; • Hardware → Networking hardware; Wireless integrated network sensors; Wireless devices.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for thirdparty components of this work must be honored. For all other uses, contact the owner/author(s).

ACM MobiCom '24, November 18–22, 2024, Washington D.C., DC, USA © 2024 Copyright held by the owner/author(s). ACM ISBN 979-8-4007-0489-5/24/11 https://doi.org/10.1145/3636534.3698868 Gateway, Backhaul Networks, Embedded Systems

#### **ACM Reference Format:**

Spanddhana Sara, Moteen Shah, Dhairya Shah, C. Rajashekar Reddy and Ambuj Varshney. 2024. GateHaul: A Gateway Architecture using Backhauling Networks to Address the Connectivity Challenges of Embedded Systems. In *The 30th Annual International Conference on Mobile Computing and Networking (ACM MobiCom '24), November 18–22, 2024, Washington D.C., DC, USA*. ACM, New York, NY, USA, 3 pages. https://doi.org/10.1145/3636534.3698868

## 1 Introduction

Wireless communication remains a challenge in the sustainable deployment of embedded systems as it is energyexpensive [12]. Emerging radio architectures [5, 7, 8] lower communication energy costs but face adoption challenges due to the need for specialized infrastructure in deployments.

Emerging radio architectures delegate the energy-intensive task of generating the transceiver's local oscillator to external infrastructure [5, 7, 8], with dedicated devices like RFID readers providing the carrier signal. However, reliance on such dedicated carrier-emitting devices, a non-standard modality, complicates the setup [17] and necessitates precise positioning of the emitter relative to the tag, further exacerbating deployment challenges. Another challenge is integrating these systems with broader computing infrastructure. Sensor data needs to be communicated to remote servers for processing, but these transmitters often rely on non-standard protocols, complicating integration. While some efforts have addressed this by supporting standard protocols [3, 9, 19] like WiFi [6] or BLE [4], offloading sensor data to remote servers for processing remains a significant unaddressed challenge. ACM MobiCom '24, November 18-22, 2024, Washington D.C., DC, USA



Figure 2: Demonstration setup includes the GateHaul prototype, a backscatter sensor, a conventional transmitter, and a computer for retrieving information.

We address these challenges by designing a gateway architecture called GateHaul. This system facilitates the collection of sensor data from low-power embedded devices, including those equipped with backscatter transmitters. GateHaul manages the intricacies of these devices, for example, by providing necessary carrier signals. Moreover, GateHaul enables the offloading of collected data even without traditional backhaul networks like cellular connections. It achieves this by using networks such as Apple's FindMy.

## 2 Background and Design

**Background.** State-of-the-art backscatter transmitters support Wi-Fi [6, 7, 10], BLE [4, 10], and ZigBee [11, 22] standards, and some can communicate over vast distances [13, 16, 18]. Recent transmitters diverge from backscatter mechanisms by designing low-power oscillators using components such as tunnel diodes [14, 15, 23]. However, the challenge of collecting data from large deployments remains unaddressed.

GateHaul also builds on progress in gateway devices for embedded systems. Zachariah [20, 21] and Dutta [2] argue that embedded devices face challenges with gateways due to heterogeneous standards, necessitating a unified gateway platform. GateHaul extends these arguments to low-power networks. Beyond traditional gateways, efforts have been made to use commodity devices as data collection mules. For instance, Apple's FindMy network uses everyday Apple devices to offload tracker information. Recent works have repurposed these networks to send custom information. GateHaul extends on these efforts, building on TagAlong [1]. Design. GateHaul receives radio waves modulated by schemes such as on-off keying, frequency shift keying, and chirps. They form basis for standards commonly used in embedded systems, such as LoRa, BLE, etc. We instantiate an early prototype of GateHaul, as shown in Figure 2. It receives transmissions from low-power transmitters using backscatter [18] or tunnel diode based mechanisms [5]. We implemented support for frequency shift keying modulation, with symbol frequencies of 80 kHz and 120 kHz, at a baud rate of 10 kbps.



(a) 2-FSK Backscattered signal

(b) 2-GFSK Traditional RF signal

Figure 3: The spectrum of signals backhauled by Gate-Haul. We backhaul the 2-FSK modulated signal from low-power embedded devices in the demonstration.



Figure 4: Packet reception rate improves with the number of mules and transmission rate at the gateway.

A commodity transceiver (TI CC1310) receives transmissions on the gateway. To support low-power transmitters that require an ambient carrier signal, we equipped the gateway to generate this signal using the CC1310's test mode, building on LoRea [18]. The gateway thus uses two CC1310 transceivers. We use a single-board computer for local processing, interfacing with the transceiver, and offloading information to the backhauling network. This ensures a low-cost, compact form factor suitable for ubiquitous deployment. In particular, we use a Raspberry Pi 4B, which is serially connected to the transceiver via UART. The gateway stores sensor information, identifies available backhauling networks, and offloads sensor data accordingly. For backhauling without conventional networks, GateHaul uses Apple's FindMy network. We compress sensor information and transmit it through bluetooth advertisements. Commodity Apple devices acting as mules receive these transmissions. The reception success rate depends on the transmission frequency and nearby mules in scanning mode. Frequent retransmissions improve the reception rates, as shown in the Figure 4.

### 3 Demonstration

We demonstrate the GateHaul gateway's ability to demodulate both a backscattered signal at 868 MHz and a conventional signal at 915 MHz, each using 2-FSK modulation. The gateway then backhauls the information using nearby Apple devices, leveraging a modified version of TagAlong [1]. We show successful retrieval of the information from a computer located at some distance away from the gateway. The demo video can be viewed at: https://youtu.be/UnxT9HFTJoQ

Acknowledgement. We thank the reviewers. This work is funded by a MoE Tier 1 grant (A-8001661-00-00), a startup grant (A-8000277-00-00), a grant from the NUS-NCS Joint Center (A-0008542-02-00), and also an unrestricted gift from Google through their Research Scholar Program (A-8002307-00-00), all hosted at the National University of Singapore. GateHaul

ACM MobiCom '24, November 18-22, 2024, Washington D.C., DC, USA

#### References

- Alex Bellon et al. 2023. TagAlong: Free, Wide-Area Data-Muling and Services. In ACM HotMobile '23.
- [2] Prabal Dutta et al. 2015. eMergence of the iot gateWaY platforM. GetMobile: Mobile Comp. and Comm. (2015).
- [3] Joshua F. Ensworth et al. 2015. Every smart phone is a backscatter reader: Modulated backscatter compatibility with Bluetooth 4.0 Low Energy (BLE) devices. In *IEEE RFID* '15.
- [4] Joshua F Ensworth et al. 2017. BLE-backscatter: Ultralow-power IoT nodes compatible with Bluetooth 4.0 low energy (BLE) smartphones and tablets. *IEEE Trans. on Microwave Theory and Techniques* (2017).
- [5] Ambuj Varshney et al. 2022. Judo: Addressing the energy asymmetry of wireless embedded systems through tunnel diode based wireless transmitters. In ACM MobiSys' 22.
- [6] Bryce Kellogg et al. 2014. Wi-fi backscatter: internet connectivity for RF-powered devices. SIGCOMM Comput. Commun. Rev. (2014).
- [7] Bryce Kellogg et al. 2016. Passive Wi-Fi: Bringing Low Power to Wi-Fi Transmissions. In USENIX NSDI '16.
- [8] Mohammad Rostami et al. 2021. MIXIQ: re-thinking ultra-low power receiver design for next-generation on-body applications. In ACM MobiCom '21.
- [9] Wei Gong et al. 2020. Multiprotocol backscatter for personal IoT sensors. In CoNEXT '20.
- [10] Vikram Iyer et al. 2016. Inter-Technology Backscatter: Towards Internet Connectivity for Implanted Devices. In ACM SIGCOMM '16.
- [11] Zhijun Li et al. 2017. WEBee: Physical-Layer Cross-Technology Communication via Emulation. In *MobiCom* '17.

- [12] Vincent Liu et al. 2013. Ambient Backscatter: Wireless Communication out of Thin Air. In SIGCOMM '13.
- [13] Yao Peng et al. 2018. PLoRa: a passive long-range data network from ambient LoRa transmissions. In Proceedings of the 2018 Conference of the ACM Special Interest Group on Data Communication (SIGCOMM '18).
- [14] C. Rajashekar Reddy et al. 2023. Beyond Broadcasting: Revisiting FM Frequency-band for Providing Connectivity to Next Billion Devices. In ENSsys '23.
- [15] Moteen Shah et al. 2023. Going Beyond Backscatter: Rethinking Low-Power Wireless Transmitters using Tunnel Diodes. In MobiCom '23.
- [16] Vamsi Talla et al. 2017. LoRa Backscatter: Enabling The Vision of Ubiquitous Connectivity. ACM IMWUT' 17 (2017).
- [17] Vamsi Talla et al. 2021. Advances and Open Problems in Backscatter Networking. *GetMobile: Mobile Comp. and Comm.* (2021).
- [18] Ambuj Varshney et al. 2017. LoRea: A Backscatter Architecture That Achieves a Long Communication Range. In SenSys '17.
- [19] Chouchang Yang et al. 2017. Riding the airways: Ultra-wideband ambient backscatter via commercial broadcast systems. In *IEEE INFO-COM'17.*
- [20] Thomas Zachariah et al. 2015. The Internet of Things Has a Gateway Problem. In ACM HotMobile '15.
- [21] Thomas Zachariah et al. 2022. The internet of things still has a gateway problem. In ACM HotMobile '22.
- [22] Pengyu Zhang et al. 2017. FreeRider: Backscatter Communication Using Commodity Radios. In CoNEXT'17.
- [23] Renjie Zhao et al. 2023. SlimWiFi: Ultra-Low-Power IoT Radio Architecture Enabled by Asymmetric Communication. In USENIX NSDI '23.